



Thermafiber® UltraBatt™ Mineral Wool Thermal Batt Insulation

PRODUCT FEATURES

Description

Mineral wool thermal batt insulation.

Basic Uses/Related Uses

Thermal batt insulation for use within various wood and steel framed exterior wall, ceiling and floor construction assemblies. For a complete list of R-values and thicknesses offered, see Sizes and R-values. UltraBatt™ can be used as a thermal barrier for foamed plastics, certified to CAN/ULC-S124.

Selection Criteria

- Enhances thermal performance
- Non-combustible
- Moisture resistant and non-deteriorating
- Non-corrosive
- Vermin resistant
- Helps conserve energy, reduce greenhouse gas emissions
- Fire resistant to temperatures above 1,093° C (2,000° F)

Sustainability Criteria

- Recycled content minimum 70%, Standard Fiber
- Bronze Material Health Certificate from Cradle to Cradle
- Contributes to credits in several green building programs such as LEED® and Green Globes®
- For more information see Environmental Product Declaration (EPD) certified by UL Environment via www.thermafiber.ca/sustainability

Applicable Standards

CAN/ULC-S702	Standard for Mineral Fibre Thermal Insulation for Buildings
ASTM C665	Standard Specification for Mineral-Fiber Blanket Thermal Insulation for Light Frame Construction and Manufactured Housing
ASTM C518	Standard Test Methods for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus
CAN/ULC-S114	Standard Method of Test for Determination of Non-combustibility in Building Materials
ASTM E136	Standard Test Method for Behavior of Materials in a Vertical Tube Furnace at 750°C
CAN/ULC-S129	Standard Method of Test for Smoulder Resistance of Insulation (Basket Method)
CAN/ULC-S102	Standard Method of Test for Surface Burning Characteristics of Building Materials and Assemblies
ASTM E84	Standard Test Method for Surface Burning Characteristics of Building Materials
CAN/ULC-S124	Standard Method of Test for the Evaluation of Protective Coverings for Foamed Plastic
ASTM C1104	Standard Test Method for Determining the Water Vapor Sorption of Unfaced Mineral Fiber Insulation
ASTM C1338	Standard Test Method for Determining Fungi Resistance of Insulation Materials and Facings
ASTM C795	Standard Specification for Thermal Insulation for Use in Contact with Austenitic Stainless Steel

Performance Criteria

Compliance	Evaluation Listing No. 14059-L Type I Type I	CCMC CAN/ULC-S702 ASTM C665
Thermal	See Sizes and R-values	ASTM C518
Fire	Non-Combustible Non-Combustible Smoulder Resistance Mean Mass Loss ≤ 0.02% Flame Spread 0; Smoke Developed 0 Flame Spread 0; Smoke Developed 0 Class A - min. 138 mm (5.5") thickness QAI Listing No. B1079	CAN/ULC-S114 ASTM E136 CAN/ULC-S129 CAN/ULC-S102 ASTM E84 CAN/ULC-S124
Moisture	Moisture Absorption < 1% by volume Fungi Resistance - Pass	ASTM C1104 ASTM C1338
Corrosion	Austenitic Steel - Non-corrosive Steel, Aluminum, Copper - Non-corrosive	ASTM C795 ASTM C665

Sizes and R-values

Thickness	RSI (m ² ·K/W)	R-value (hr·ft ² ·°F/Btu)	Width	Length
Wood-framed applications				
89 mm (3.5")	2.5	14	381 mm (15") 584 mm (23")	1194 mm (47")
140 mm (5.5")	3.9	22		
146 mm (5.75")	4.2	24		
180 mm (7.1")	4.9	28		
203 mm (8.0")	5.6	32		
Steel-framed applications				
64 mm (2.5")	1.8	10	406 mm (16") 610 mm (24")	1219 mm (48")
89 mm (3.5")	2.5	14		
152 mm (6.0")	4.0/4.2	22.5/24		

Quality Statement, Tests, Certifications and Approvals

- Fire resistance verified by QAI - QAI Listing No. B1079-1.
- Recycled content verified by ICC-ES.

Delivery and Storage

Deliver products in their original packages, and store in enclosed shelter.

Limitations

Packaging is not UV resistant. Shelter unused packages from the elements.

Safety

Contact with mineral wool may cause temporary eye and skin irritation. Wear eye protection and long-sleeved loose fitting clothing closed at the neck and wrists. For additional information refer to the Safe Use Instruction Sheet (SUIS) found in the SDS Database via <http://sds.owenscorning.com>.

Availability/Cost

Contact Owens Corning local Area Sales Manager. See ASM territory map via www.thermafiber.ca/contact.





Thermafiber® UltraBatt™

Mineral Wool Thermal Batt Insulation



PRODUCT PROPERTIES

Materials

Mineral wool, Type I (to CAN/ULC-S702), non-combustible (to CAN/ULC-S114), non-corrosive (to ASTM C665).

PRODUCT PLACEMENT

Installation

- Install in accordance with Thermafiber® insulation installation instructions as shown on packaging.
- Batts are typically installed friction-fit between framing members in wall and floor assemblies.
- Batts should be butted tight at joints, filling all voids, do not over compress.
- Cut insulation with a serrated knife for custom fitting.

Coverage

RSI (m ² -K/W)	R-value (hr-ft ² -°F/Btu)	Batts per Bag	Width	Coverage per Bag	
				sq. m.	sq. ft.
Wood-framed applications: 1194 mm (47") Length					
2.5	14	5	381 mm (15")	2.27	24.5
			584 mm (23")	3.49	37.5
3.9/4.2	22/24	4	381 mm (15")	1.82	19.6
			584 mm (23")	2.79	30.0
4.9/5.6	28/32	3	381 mm (15")	1.36	14.7
			584 mm (23")	2.09	22.5

RSI (m ² -K/W)	R-value (hr-ft ² -°F/Btu)	Batts per Bag	Width	Coverage per Bag	
				sq. m.	sq. ft.
Steel-framed applications: 1219 mm (48") Length					
1.8	10	8	406 mm (16")	3.96	42.7
			610 mm (24")	5.95	64.0
2.5	14	5	406 mm (16")	2.47	26.7
			610 mm (24")	3.72	40.0
4.0/4.2	22.5/24	4	406 mm (16")	1.98	21.3
			610 mm (24")	2.97	32.0

Technical Services Available

For Canadian Thermafiber® Technical inquiries please contact Matthew Schiedel: matthew.schiedel@owenscorning.com or at 1-844-304-1623



Current Ed: 2018.09.01
Previous Ed: 2017.05.01



Disclaimer of Liability

Thermafiber, Inc. shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Thermafiber, Inc. liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing within thirty (30) days from date it was or reasonably should have been discovered.

LEED® is a registered trademark of the U.S. Green Building Council.
Green Globes® is a registered trademark of Green Building Initiative, Inc.

THERMAFIBER, INC.
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659
1-800-GET-PINK®
www.thermafiber.ca

Pub. No. 600004A Printed in Canada. September 2018.
THE PINK PANTHER™ & © 1964–2018 Metro-Goldwyn-Mayer Studios Inc.
All Rights Reserved. The colour PINK is a registered trademark of Owens Corning.
© 2018 Owens Corning. All Rights Reserved. © 2018 Thermafiber, Inc.
All Rights Reserved.

